








XNT Soldering Tip Family

- + Most difficult, high mass soldering jobs
- + Maximum power and response for top performance
- + Optimal balance between power, control and running costs with wide range of tips
- + Highest quality soldering standard for widest range of applications



Chisel 	<table><thead><tr><th>Article</th><th></th><th>a / b (mm) / (inch)</th></tr></thead><tbody><tr><td>XNT A T0054485199</td><td> BESTSELLER </td><td>1.6 mm / 0.4 mm 0.063 inch / 0.016 inch</td></tr><tr><td>XNT AX T0054486499</td><td></td><td>1.6 mm / 0.8 mm 0.063 inch / 0.315 inch</td></tr><tr><td>XNT B T0054485799</td><td> BESTSELLER </td><td>2.4 mm / 0.8 mm 0.094 inch / 0.315 inch</td></tr><tr><td>XNT BX T0054488299</td><td></td><td>2.4 mm / 0.8 mm 0.094 inch / 0.315 inch</td></tr><tr><td>XNT C T0054485899 only US</td><td></td><td>3.2 mm / 0.8 mm 0.126 inch / 0.315 inch</td></tr></tbody></table>	Article		a / b (mm) / (inch)	XNT A T0054485199	BESTSELLER 	1.6 mm / 0.4 mm 0.063 inch / 0.016 inch	XNT AX T0054486499		1.6 mm / 0.8 mm 0.063 inch / 0.315 inch	XNT B T0054485799	BESTSELLER 	2.4 mm / 0.8 mm 0.094 inch / 0.315 inch	XNT BX T0054488299		2.4 mm / 0.8 mm 0.094 inch / 0.315 inch	XNT C T0054485899 only US		3.2 mm / 0.8 mm 0.126 inch / 0.315 inch																					
Article		a / b (mm) / (inch)																																						
XNT A T0054485199	BESTSELLER 	1.6 mm / 0.4 mm 0.063 inch / 0.016 inch																																						
XNT AX T0054486499		1.6 mm / 0.8 mm 0.063 inch / 0.315 inch																																						
XNT B T0054485799	BESTSELLER 	2.4 mm / 0.8 mm 0.094 inch / 0.315 inch																																						
XNT BX T0054488299		2.4 mm / 0.8 mm 0.094 inch / 0.315 inch																																						
XNT C T0054485899 only US		3.2 mm / 0.8 mm 0.126 inch / 0.315 inch																																						
Round 	<table><thead><tr><th colspan="3">Round</th></tr></thead><tbody><tr><td>XNT 1L T0054487199</td><td></td><td>0.2 mm 0.008 inch</td></tr><tr><td>XNT 1LX T0054487299</td><td></td><td>0.2 mm 0.008 inch</td></tr><tr><td>XNT 1S T0054485299</td><td></td><td>0.2 mm 0.008 inch</td></tr><tr><td>XNT 1SLX 45° T0054487599</td><td></td><td>0.4 mm 0.016 inch</td></tr><tr><td>XNT 1X T0054486599</td><td></td><td>0.4 mm 0.016 inch</td></tr><tr><td>XNT AS T0054486999 only US</td><td></td><td>1.6 mm 0.063 inch</td></tr></tbody></table> <table><thead><tr><th colspan="3">Round, sloped 45°</th></tr></thead><tbody><tr><td>XNT 4 T0054485599</td><td></td><td>1.2 mm 0.047 inch</td></tr><tr><td>XNT AA 45° T0054488499</td><td></td><td>1.6 mm 0.063 inch</td></tr><tr><td>XNT BB 45° T0054488599</td><td></td><td>2.4 mm 0.094 inch</td></tr><tr><td>XNT CC 45° T0054488699</td><td></td><td>3.2 mm 0.126 inch</td></tr><tr><td>XNT F 45° T0054488799</td><td></td><td>1.2 mm 0.047 inch</td></tr></tbody></table>	Round			XNT 1L T0054487199		0.2 mm 0.008 inch	XNT 1LX T0054487299		0.2 mm 0.008 inch	XNT 1S T0054485299		0.2 mm 0.008 inch	XNT 1SLX 45° T0054487599		0.4 mm 0.016 inch	XNT 1X T0054486599		0.4 mm 0.016 inch	XNT AS T0054486999 only US		1.6 mm 0.063 inch	Round, sloped 45°			XNT 4 T0054485599		1.2 mm 0.047 inch	XNT AA 45° T0054488499		1.6 mm 0.063 inch	XNT BB 45° T0054488599		2.4 mm 0.094 inch	XNT CC 45° T0054488699		3.2 mm 0.126 inch	XNT F 45° T0054488799		1.2 mm 0.047 inch
Round																																								
XNT 1L T0054487199		0.2 mm 0.008 inch																																						
XNT 1LX T0054487299		0.2 mm 0.008 inch																																						
XNT 1S T0054485299		0.2 mm 0.008 inch																																						
XNT 1SLX 45° T0054487599		0.4 mm 0.016 inch																																						
XNT 1X T0054486599		0.4 mm 0.016 inch																																						
XNT AS T0054486999 only US		1.6 mm 0.063 inch																																						
Round, sloped 45°																																								
XNT 4 T0054485599		1.2 mm 0.047 inch																																						
XNT AA 45° T0054488499		1.6 mm 0.063 inch																																						
XNT BB 45° T0054488599		2.4 mm 0.094 inch																																						
XNT CC 45° T0054488699		3.2 mm 0.126 inch																																						
XNT F 45° T0054488799		1.2 mm 0.047 inch																																						
Conical 	<table><tbody><tr><td>XNT 1 T0054485099</td><td> BESTSELLER </td><td>0.5 mm 0.02 inch</td></tr><tr><td>XNT S T0054486899</td><td></td><td>0.4 mm 0.016 inch</td></tr></tbody></table>	XNT 1 T0054485099	BESTSELLER 	0.5 mm 0.02 inch	XNT S T0054486899		0.4 mm 0.016 inch	Measuring tip  T0054486199N																																
XNT 1 T0054485099	BESTSELLER 	0.5 mm 0.02 inch																																						
XNT S T0054486899		0.4 mm 0.016 inch																																						

Power Response



Component size

XS

 to

M

Heat up time

°C

350

300

200

100

0

5 Sec.*

*from 50°C to 350°C / 120°F to 620°F

High mass soldering jobs



Weller®

weller-tools.com/toolselector/en
weller-tools.com/toolselector/us