

Smock AM-160 with Applications

(Part No.: 2618.AM160.x)

- Static dissipative smock for use in ESD protected areas
- Complies with IEC 61340-5-1
- Lightweight, breathable and comfortable
- Tailored in 3/4 design
- Easy snap fastening, hidden snaps
- Conductive yarn woven through the fabric in 4mm grid
- Unisex sizes in XS - 5XL
- Folded sleeves fixture with a snap



Colour:	blue/dark blue (2618.AM160.B) white/blue (2618.AM160.W) grey/bordeaux (2618.AM160.G.BX) grey/black (2618.AM160.G) white/bordeaux (2618.AM160.W.BX)
Design:	Long and folded sleeves, one breast pocket with ESD-logo and application, two side pockets with application
Material:	65 % polyester, 32 % cotton, 3 % carbon coated yarn
Weight:	156 g/m ² ± 3 %



Durability:

Keep the electrical properties according to IEC 61340-5-1 after 50 normal washing cycles.

Washing instructions:

- Machine washable, up to 60 °C
- Do not bleach
- Medium heat ironing, max. 150 °C
- Tumble dry, normal, low heat
- Do not allow contact with strong acids or alkali



Product qualification according to IEC 61340-5-1:

	Test method	Limits	Typical values
Point to Point resistance R_{p-p}	IEC 61340-4-9	$< 1 \times 10^{11} \Omega$	$10^5 - 10^7 \Omega$
Environmental conditions: $12 \pm 3 \% RH$ and $23 \pm 2 ^\circ C$ (conditioning > 48 hours)			

Important information for fitting of clothes:

Please use always already laundered clothes!