







VD 2200 ESD

Safety shoe EN ISO 20345:2011 S1 SRC

Sizes: 36 - 48/49 (225 - 315)

- + Light-weight textile upper combined with breathable textile inserts
- + Perforated design for optimal ventilation
- + Aluminum toe cap

Fitting Options: NB, XB (S, XXB)

- + Breathable, functional lining
- + Leather insole
- + Full-length, removable insole ERGO-SOFT ESD with additional cushioning effect and excellent moisture transportation

TPU Dynamics ESD, white

- + Outsole with a profile of 2,6 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120° C



Multi-zone shock absorption VARIO Vitality®

The VARIO Vitality® weight dependent multi-zone shock absorption combined with SECURA VARIO® heel shock absorption with a special damping element in the ball and toe area. This gives a soft feel and reduces pressure loads in the shoe, thus relieving the back and forefoot.





Certified and recommended by Association Forum Healthy Back - Better living and Federal Association of German Back Schools.

More information: AGR e. V. · P.O. Box 103 · D-27443 Selsingen Phone +49 4284 92 69 990 · www.agr-ev.de






multi-width system












STEITZ FLEX-ZONE®
















Highly flexible, metall free puncture resistance













Subject to technical modifications.

sizes.

Different soles may be used for extreme

