



- Unit purifies air at up to 4 workplaces
- Constant Flow Control (CFC) guarantees automatical air flow regulation for each working place independent of the connected workplaces
- Electronic filter control with optical and acoustic filter alarm
- Efficiency test via USB port
- 4 wheels to allow easy movement of the unit
- Low noise level
- 4 kits available
- The fume extraction unit Zero Smog 4V (ZS 4V) is easy to install and operate. It is designed for use as a small central system. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m³/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.

## Zero Smog 4V

Code No.: T0053660699

|                                  |   |
|----------------------------------|---|
| Dimensions W x D x H (mm)        | 345 x 325 x 505   |
| Dimensions W x D x H (Inch)      | 13,58x12,79x19,88   |
| Weight (ca) in kg                | 19  |
| Voltage                          | 220-240 V (50/60 Hz)  |
| Heating output                   | 275 VA  |
| Noise level (distance 1 m) dB(A) | < 48  |
| Max. vacuum                      | ---   |
| Capacity m³/h                    | 230   |
| Pre filter                       | Pre filter mat class F7   |
| Cartridge Volume Extraction      | Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb) |
| Max. capacity                    | 1-4 workplaces  |
| Interface RS232 (Remote control) | All system functions can be operated and remotely monitored via the RS232 port. |
| USB interface                    | on  |
| WX compatible                    | on  |